



## HAMACHI SWIRL

### Physical Properties

Weight: Type II 20 oz  
Content: 100% Vinyl  
Backing: Osnaburg  
Width: 52/54"  
Repeat: Random Reverse

### Performance:

Fire Rating: Class A, ASTM E84  
Europe CE Fire Tested  
Color Fastness UK Test Result: BS2782-Pass  
Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

### Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)  
NSF 342

Product contains up to 40% recycled content  
Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA  
Printed with Solvent-Free Inks  
This product has a CE Declaration of of Conformity.

### Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

**Manufactured in the USA**

### Available in 9 Colorways

CM98-2084 Cream	CM98-2089 Lacquer
CM98-2085 Champagne	CM98-2090 Pewter
CM98-2086 Alabster	CM98-2091 Chocolate
CM98-2087 Dust	CM98-2092 Ebony
CM98-2088 Bark	

