

COMMAND

WALLCOVERINGS



KOTO

Physical Properties

Weight: Type II 20 oz
Content: 100% Vinyl
Backing: Osnaburg
Width: 52/54"
Repeat: Random Match

Performance:

Fire Rating: Class A, ASTM E84
Europe CE Fire Tested
Color Fastness UK Test Result: BS2782-Pass
Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)
NSF 342
Product contains up to 40% recycled content
Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA
Printed with Solvent-Free Inks
This product has a CE Declaration of of Conformity.

Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

Manufactured in the USA

Available in 12 Colorways

| | |
|---------------------|----------------------|
| CM127-2528 Pearl | CM127-2534 Cool Grey |
| CM127-2529 Snow | CM127-2535 Taupe |
| CM127-2530 Fog | CM127-2536 Stone |
| CM127-2531 Bourbon | CM127-2537 Brick |
| CM127-2532 Graphite | CM127-2538 Plum |
| CM127-2533 Brindle | CM127-2539 Indigo |

