



ARGONNE SILK

Physical Properties

Weight: Type II 20 oz
Content: 100% Vinyl
Backing: Osnaburg
Width: 52/54"
Repeat: Random Match

Performance:

Fire Rating: Class A, ASTM E84
Europe CE Fire Tested
Color Fastness UK Test Result: BS2782-Pass
Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)
NSF 342

Product contains up to 40% recycled content
Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA
Printed with Solvent-Free Inks
This product has a CE Declaration of of Conformity.

Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

Manufactured in the USA

Available in 18 Colorways

CM105-2181 Fresh Air	CM105-2190 Lynx
CM105-2182 Ivory Billed	CM105-2191 Fern Canyon
CM105-2183 Butter	CM105-2192 Tucumcari
CM105-2184 Snowdrift	CM105-2193 Gravelstone
CM105-2185 Pacific Coast	CM105-2194 Loblolly Pine
CM105-2186 Emberlight	CM105-2195 Mineral
CM105-2187 Silver Mist	CM105-2196 Smokey Blue
CM105-2188 Rainwashed	CM105-2197 Navy Pier
CM105-2189 Fennec	CM105-2198 Tephra