



## KOTO

### Physical Properties

Weight: Type II 20 oz  
Content: 100% Vinyl  
Backing: Osnaburg  
Width: 52/54"  
Repeat: Random Match

### Performance:

Fire Rating: Class A, ASTM E84  
Europe CE Fire Tested  
Color Fastness UK Test Result: BS2782-Pass  
Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

### Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)  
NSF 342  
Product contains up to 40% recycled content  
Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA  
Printed with Solvent-Free Inks  
This product has a CE Declaration of of Conformity.

### Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

### Manufactured in the USA

### Available in 12 Colorways

CM127-2528 Pearl	CM127-2534 Cool Grey
CM127-2529 Snow	CM127-2535 Taupe
CM127-2530 Fog	CM127-2536 Stone
CM127-2531 Bourbon	CM127-2537 Brick
CM127-2532 Graphite	CM127-2538 Plum
CM127-2533 Brindle	CM127-2539 Indigo