

COMMAND

WALLCOVERINGS



WEFT

Physical Properties

Weight: Type II 20 oz

Content: 100% Vinyl

Backing: Osnaburg

Width: 52/54"

Repeat: Random Reversible

Performance:

Fire Rating: Class A, ASTM E84

Europe CE Fire Tested

Color Fastness UK Test Result: BS2782-Pass

Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)

NSF 342

Product contains up to 40% recycled content

Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA

Printed with Solvent-Free Inks

This product has a CE Declaration of of Conformity.

Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue please consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

Manufactured in the USA

Available in 16 Colorways

CM111-2279 White	CM111-2287 Ginger
CM111-2280 Bisque	CM111-2288 Claret
CM111-2281 Dove	CM111-2289 Taupe
CM111-2282 Linen	CM111-2290 Burlap
CM111-2283 Hemp	CM111-2291 Greige
CM111-2284 Straw	CM111-2292 Flannel
CM111-2285 Key Lime	CM111-2293 Charcoal
CM111-2286 Caribo	CM111-2294 Indigo

