



## TUSSAR SILK

### Physical Properties

Weight: Type II 20 oz

Content: 100% Vinyl

Backing: Osnaburg

Width: 52/54"

Repeat: Random match

### Performance:

Fire Rating: Class A, ASTM E84

Europe CE Fire Tested

Color Fastness UK Test Result: BS2782-Pass

Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

### Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)

NSF 342

Product contains up to 40% recycled content

Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA

Printed with Solvent-Free Inks

This product has a CE Declaration of of Conformity.

### Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue please consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

### Manufactured in the USA

### Available in 21 Colorways

CM163-2974 FAIRY DUST	CM163-2985 SUN&SHADOW
CM163-2975 LINEN	CM163-2986 LAGUNA
CM163-2976 FEATHER	CM163-2987 STORM
CM163-2977 STONE	CM163-2988 FERN
CM163-2978 MULBERRY	CM163-2989 LATTE
CM163-2979 GRANITE	CM163-2990 DUNE
CM163-2980 ALMOND	CM163-2991 STRAW
CM163-2981 ESPESSO	CM163-2992 BARK
CM163-2982 PAPAYA	CM163-2993 EMERALD GREY
CM163-2983 PEARL	CM163-2994 MIDNIGHT
CM163-2984 GREIGE	*Mylar/non-woven   2520, 2524, 2527